



PLK-G1306

Electronically controlled small area sewing machine with large shuttle hook. Economy model with single stage air clamp and air presser foot. Sewing area 130x60mm



PLK-G1306

PLK-G1306



This machine uses G-series electronics with USB memory for pattern storage as well as an internal memory. The machine is equipped with a simple operation panel however there is an optional touch screen for making sewing patterns and customizing parameters. The presser foot is air operated and mechanically adjusted according to the material thickness. The drive motor is mounted under the table like the previous PLK-E series machines. Optional 2-stage conversion kit offers the possibility to use the left and right clamp independently.

Specifications

MODEL	PLK-G1306
Stitch Type	Single Needle Lockstitch
Sewing Area	(X) 130mm x (Y) 60mm (5 3/16" x 2 3/8")
Max. Speed	2000 rpm (Depending on Application)
Feeding System	Intermittent or Continuous
Stitch Length	0.1~20.0mm (Min. Resolution 0.1mm)
Pattern Storage	Internal Memory or External USB
Max. Number of Stitches	20,000 Stitches per Pattern
Max. Number of Patterns	900 Patterns (Internal Memory)
Scale Up / Scale Down	10~200% for X and Y axis
Presser Foot	Air Actuated (Mechanical Adjustment)
Hook	Shuttle/Large/Size R Bobbin
Needle	135 x 17 Size #18
Work Holder Lift	Max. 25mm
Presser Foot Lift	Max. 15mm
Operation Panel	PLK-G10 (Optional PLK-G-PAL)
Main Driving Motor	550 Watt (Under the Table Mounted)
Power	220 Volt / Single or 3 Phase
Clamp	Air Actuated/Single Stage
Mass	133 kg

Applications

Attaching webbing, labels, velcro, etc. on various operations on apparel, automotive, and military applications.



PLK-G10



Optional
PLK-G-PAL

